

wiTECH 2.0 System - Network Requirements

Article Number: 260 | Rating: Unrated | Last Updated: Mon, Feb 11, 2019 9:20 PM

All wiTECH IP addresses should allow and have access to the following domains and all of its sub-domains through ports 53, 80, 443, 541,1677,8443, 514 and 8070 traffic to the internet for the proper function of wiTECH 2.0 System.

- *.fcawitech.com
- *.amazonaws.com
- *s3.amazonaws.com
- *.mixpanel.com
- *.bugsnag.com
- *.witech2.com
- *.dcctools.com
- *.dealerconnect.chrysler.com
- *.edgesuite.net
- *.adobe.com
- *.akamai.com
- *.akamaiedge.com
- *.chrysler.com
- *.dealerconnect.com
- *.dodge.com
- *.edgesuite.net
- *.java.com
- *.jeep.com
- *.sun.com
- *.wiadvisor.com
- *.witechsystem.com
- *.wiadvisor.dcctools.com
- <http://fonts.googleapis.com/css?family=Roboto:400,300>



**WI
TECH 2.0**

The firewall also needs to allow .zip files from the above mentioned websites. If you have any questions, please contact wiTECH Support.

SD-WAN or similar networking products employed by the dealership must permit the origin security certificates to pass through unchanged.

Posted : Alex Richmond - Mon, Sep 28, 2015 5:31 PM. This article has been viewed 15924 times.

Online URL: <https://kb.fcawitech.com/article/witech-2-0-system-network-requirements-260.html>